

Model	M-12		M-18		MX-18		M-20		M-26		M-32		MS-20
Tip	Sladkovodni		Sladkovodni		Sladkovodni		Sladkovodni		Sladkovodni		Sladkovodni		Slana voda
Statični potisk	30lb	13.6 kg	40lb	18.2 kg	40lb	18.2 kg	45lb	20.4 kg	55lb	25.0 kg	700lb	31.8 kg	45lb 20.4 kg
Dolžina osi	30"	762mm	36"	914mm	36"	914mm	36"	914mm	36"	914mm	42"	1067mm	36" 914mm
Napetost (V)	12		12		12		12		12		24		12
Max Amperaža (A)	30		42		42		42		50		42		42
Upravljanje hitrosti naprej / nazaj	5 NAP / 3 NAZ		5 NAP / 3 NAZ		Variabilno		5 NAP / 3 NAZ		Variabilno		Variabilno		Variabilno
Ročica	Teleskopska		Teleskopska		Teleskopska		Tilt / Raztegljiva		Tilt / Raztegljiva		Tilt / Raztegljiva		Teleskopska
Digitalni Maximizer	Ne		Ne		Da		Ne		Da		Da		Da
Prikaz napolnjenosti akumulatorja	Da		Da		Da		Da		Da		Da		Da
Teža	7kg		8kg		12kg		10kg		11kg		12kg		11kg
Kompozitna os	Da		Da		Da		Da		Da		Da		Da
MPC € z DDV 22%	219,00		319,00		419,00		429,00		729,00		849,00		589,00

Krško, 09.03.2020



Teža plovila		Max dolžina plovila		Priporočen nivo potiska		Potrebne baterije
< 1500lb	< 680 kg	14'	4.2m	30lb	13.6 kg	1 baterija (12v)
2000lb	900 kg	18'	5.5m	40-45lb	18.2 - 20.4 kg	1 baterija (12v)
2500lb	1135 kg	21'	6.4m	55lb	25 kg	1 baterija (12v)
3000 - 3500lb	1360 - 1587 kg	23'	7.0m	70lb	31.8 kg	2 bateriji (24v)

Višina krme do vode		Priporočena dolžina osi	
0-10"	0-25cm	30"	762mm
10-16"	25-40cm	36"	914mm
16-22"	40-56cm	42"	1067mm

TRANSOM GUIDE

